

1523A Coax - CATV Cable



For more Information
please call

1-800-Belden1



Description

Series 11, 14 AWG solid .064" bare copper-covered steel conductor, gas-injected foam polyethylene insulation, Duobond® II + aluminum braid shield (60% coverage), PVC jacket.

Physical Characteristics (Overall):

Conductor:

AWG

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
1	14	Solid	BCCS - Bare Copper Covered Steel	0.064

Insulation:

Insulation Material

Insulation Material	Dia. (in.)
Gas-injected FPE - Foam Polyethylene	0.280

Outer Shield:

Outer Shield Material

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Duobond®	Tape	Bonded Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	AL - Aluminum	60

Outer Jacket:

Outer Jacket Material

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cabling:

Overall Nominal Diameter: .400 in.

Mechanical Characteristics (Overall):

Operating Temperature Range -40°C To +80°C

Non-UL Temperature Rating 80°C

Bulk Cable Weight: 54 lbs/1000 ft.

Max. Recommended Pulling Tension: 260 lbs.

Min. Bend Radius (Install)/Minor Axis: 4.500 in.

Applicable Specifications and Agency Compliance (Overall):

Applicable Standards:

NEC/(UL) Specification CM, CATV

CEC/C(UL) Specification CM

EU CE Mark (Y/N) Yes

EU RoHS Compliant (Y/N) Yes

EU RoHS Compliance Date (mm/dd/yyyy) 01/01/2004

Series Type Series 11

Flame Test:

UL Flame Test UL1685 UL Loading

Plenum/Non-Plenum:

Plenum (Y/N)

N

Electrical Characteristics (Overall):

Nom. Characteristic Impedance

Impedance (Ohm)
75.000

Nom. Inductance

Inductance (µH/ft)
0.097

Maximum Capacitance Conductor to Shield

Capacitance (pF/ft)
16.200

Nominal Velocity of Propagation

VP (%)
83

Nominal Delay

Delay (ns/ft)
1.200

Nom. Conductor DC Resistance

DCR @ 20°C (Ohm/1000 ft)
11.000

Nominal Outer Shield DC Resistance

DCR @ 20°C (Ohm/1000 ft)
4.100

Max. Attenuation

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Attenuation (dB/100 ft.)
	5.000			0.380
	55.000			0.970
	211.000			1.810
	270.000			2.050
	300.000			2.150
	350.000			2.320
	400.000			2.470
	450.000			2.650
	550.000			2.940
	750.000			3.500
	870.000			3.840
	1000.000			4.230

Max. Operating Voltage - UL

Voltage
300 V RMS

Max. Operating Voltage - Non-UL

Voltage
300 V RMS

Minimum Structural Return Loss

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Min. SRL (dB)
		5.000	1000.000	20.000

Notes (Overall):

Notes Sweep tested 5 MHz to 1 GHz.

PUT UPS AND COLORS:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1523A 0091000	1,000 FT	66.000 LB	WHITE	C	#14 GIFHDLDPPE SH PVC WHT
1523A 0101000	1,000 FT	66.000 LB	BLACK		#14 GIFHDLDPPE SH PVC BLK

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 05-14-2007

© 2007 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory; and China Ministry of Information Industry order#39 (China RoHS). EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.