

8422 Non-Paired - Microphone and Musical Instrument Cable



Description:

22 AWG stranded (16x34) high-conductivity tinned copper conductors, polyethylene insulation, conductors cabled, cotton braid, tinned copper braid shield (85% coverage), PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Conductors	2
Total Number of Conductors	2
AWG	22
Stranding	16x34
Conductor Diameter	.031 in.
Conductor Material	High Conductivity TC - Tinned Copper

INSULATION:

Insulation Material	PE - Polyethylene
Nom. Insulation Wall Thickness	.021 in.
Insulation Diameter	.072 in.

OVERALL CABLING:

Overall Cabling Color Code Chart :

Number	Color
1	Clear
2	Black

Overall Cabling Separator Material	Cotton Braid
------------------------------------	--------------

OUTER SHIELD:

Outer Shield Type	Braid
Outer Shield Material	TC - Tinned Copper
Outer Shield % Coverage	85 %

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
Outer Jacket Nominal Wall Thickness	.022 in.

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.231 in.
--------------------------	----------

8422 Non-Paired - Microphone and Musical Instrument Cable

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-40°C To +80°C
Non-UL Temperature Rating	80°C
Bulk Cable Weight	29.6 lbs/1000 ft.
Max. Recommended Pulling Tension	93 lbs.
Min. Bend Radius (Install)	2.3 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	90 Ohms
Nom. Inductance	.22 µH/ft
Nom. Capacitance Conductor to Conductor @ 1 KHz	18 pF/ft
Nom. Cap. Cond. to Other Cond. & Shield @ 1 KHz	32 pF/ft
Nominal Outer Shield DC Resistance @ 20 Deg. C	3.5 Ohms/1000 ft
Max. Operating Voltage - Non-UL	1000 V RMS
Other Maximum Continuous Currents	2.9 Amps per conductor @ 25°C

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
8422 0601000	2 #22 PE SHLD PVC	1000	31	CHROME	C
8422 060500	2 #22 PE SHLD PVC	500	15.5	CHROME	
8422 060U1000	2 #22 PE SHLD PVC	U1000	30	CHROME	

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 10-28-2003

© 2003 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.