

HOOK - UP WIRE

**Philmore Hook-up Wire
UL Style 1007/1569
Insulated copper wire
Solid and stranded types.**

Philmore offers all of the most called for gauges in UL listed, 300 volt hook-up wire for use in electronic and electrical circuits. Ten colors in wire gauges 26 through 16 AWG and your choice of 25 or 100 foot spools.

SPECIFICATIONS	
STRANDED TINNED COPPER	
PVC INSULATION (10 COLORS) .016"	
UL STYLE 1007/1569 VM-1	
CSA TR-64	
TEMPERATURE -40 to 105° C.	
Rated 300 volts	



**26 AWG STRANDED .051 nom.
OD 7X34 strands**

Color	25 ft. Spool	100 ft. Spool
Black	78-22610	78-22640
Brown	78-22611	78-22641
Red	78-22612	78-22642
Orange	78-22613	78-22643
Yellow	78-22614	78-22644
Green	78-22615	78-22645
Blue	78-22616	78-22646
Violet	78-22617	78-22647
Gray	78-22618	78-22648
White.	78-22619	78-22649

**24 AWG STRANDED .056 nom.
OD 7X34 strands**

Color	25 ft. Spool	100 ft. Spool
Black	78-22410	78-22440
Brown	78-22411	78-22441
Red	78-22412	78-22442
Orange	78-22413	78-22443
Yellow	78-22414	78-22444
Green	78-22415	78-22445
Blue	78-22416	78-22446
Violet	78-22417	78-22447
Gray	78-22418	78-22448
White.	78-22419	78-22449

**22 AWG STRANDED .062" nom.
OD 7X30 strands**

Color	25 ft. Spool	100 ft. Spool
Black	78-22210	78-22240
Brown	78-22211	78-22241
Red	78-22212	78-22242
Orange	78-22213	78-22243
Yellow	78-22214	78-22244
Green	78-22215	78-22245
Blue	78-22216	78-22246
Violet	78-22217	78-22247
Gray	78-22218	78-22248
White.	78-22219	78-22249

**20 AWG STRANDED .069" nom.
OD 10X30 strands**

Color	25 ft. Spool	100 ft. Spool
Black	78-22010	78-22040
Brown	78-22011	78-22041
Red	78-22012	78-22042
Orange	78-22013	78-22043
Yellow	78-22014	78-22044
Green	78-22015	78-22045
Blue	78-22016	78-22046
Violet	78-22017	78-22047
Gray	78-22018	78-22048
White.	78-22019	78-22049

**18 AWG STRANDED .077" nom.
OD 16X30 strands**

Color	25 ft. Spool	100 ft. Spool
Black	78-21810	78-21840
Brown	78-21811	78-21841
Red	78-21812	78-21842
Orange	78-21813	78-21843
Yellow	78-21814	78-21844
Green	78-21815	78-21845
Blue	78-21816	78-21846
Violet	78-21817	78-21847
Gray	78-21818	78-21848
White.	78-21819	78-21849

**16 AWG STRANDED .092" nom.
OD 26X30 strands**

Color	25 ft. Spool	100 ft. Spool
Black	78-21610	78-21640
Brown	78-21611	78-21641
Red	78-21612	78-21642
Orange	78-21613	78-21643
Yellow	78-21614	78-21644
Green	78-21615	78-21645
Blue	78-21616	78-21646
Violet	78-21617	78-21647
Gray	78-21618	78-21648
White.	78-21619	78-21649

24 AWG SOLID Copper insulated

SPECIFICATIONS	
SOLID COPPER	
PVC INSULATION (10 COLORS)	
.016" Insulation thickness	
UL STYLE 1007/1569 VM-1	
CSA TR-64	
TEMPERATURE -40 to 105° C.	
Rated 300 volts	

Color	25 ft. Spool	100 ft. Spool
Black	78-12410	78-12440
Brown	78-12411	78-12441
Red	78-12412	78-12442
Orange	78-12413	78-12443
Yellow	78-12414	78-12444
Green	78-12415	78-12445
Blue	78-12416	78-12446
Violet	78-12417	78-12447
Gray	78-12418	78-12448
White.	78-12419	78-12449

22 AWG SOLID Copper insulated

Color	25 ft. Spool	100 ft. Spool
Black	78-12210	78-12240
Brown	78-12211	78-12241
Red	78-12212	78-12242
Orange	78-12213	78-12243
Yellow	78-12214	78-12244
Green	78-12215	78-12245
Blue	78-12216	78-12246
Violet	78-12217	78-12247
Gray	78-12218	78-12248
White.	78-12219	78-12249

20 AWG SOLID Copper insulated

Color	25 ft. Spool	100 ft. Spool
Black	78-12010	78-12040
Brown	78-12011	78-12041
Red	78-12012	78-12042
Orange	78-12013	78-12043
Yellow	78-12014	78-12044
Green	78-12015	78-12045
Blue	78-12016	78-12046
Violet	78-12017	78-12047
Gray	78-12018	78-12048
White.	78-12019	78-12049

18 AWG SOLID Copper insulated

Color	25 ft. Spool	100 ft. Spool
Black	78-11810	78-11840
Brown	78-11811	78-11841
Red	78-11812	78-11842
Orange	78-11813	78-11843
Yellow	78-11814	78-11844
Green	78-11815	78-11845
Blue	78-11816	78-11846
Violet	78-11817	78-11847
Gray	78-11818	78-11848
White.	78-11819	78-11849