


# 5400A SERIES CONTACTORS WITH TURN-LOCK PHOTOCONTROL



## SPECIFICATIONS

**RECEPTACLE:** 3-prong turn-lock meets the requirements of EEL NEMA.

**POWER CONSUMPTION:** Maximum 3 watts during daylight.

## APPLICATIONS



- For street lighting. Controls all lighting loads in excess of the capacity of the photoelectric control contacts.

## FEATURES


**OPERATION:** Delay up to two minutes to prevent false switching due to light from passing vehicles, lighting, etc. Photocontrol provides dusk to dawn control of lighting contactor for heavy duty switching.

**STANDARDS:** Meets UL773 and ANSI C136.10 for photocontrols.

**HOUSING:** Outdoor NEMA Type 3R. Beige enamel finish. Two 1/2"– 3/4" combination KO in bottom.

CAT. NO.	UPC CODE	PHOTOCONTROL INCLUDED	VOLTAGE (VAC) 60Hz	SWITCH
5403A	81012	2005B	120	DPST
5404A	81013	2007B	208-240	DPST
5404-3A	81014	2007B	277	DPST

TYPE	VOLTAGE (VAC)	CONTACT RATING PER POLE
Resistive	120-277	40A
Tungsten	120	30A
Ballast	120-277	40A
LED	120-277	40A
Motor	120 240	3HP 7.5HP



## 5400A SERIES

